

2*LTE MIMO/ GPS/ WIFI All-in-one Multiple Antenna



—— Model No.: AC564 ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- All-in-one multiple antenna, including 2*LTE MIMO & GPS & WIFI
- WIFI double band 2.4GHz / 5GHz
- IP69K Waterproof
- SMA Male connector type with 3m (9.84ft) cable length
- 3M adhesive and fastened by three self-tapping screws

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

2 LTE MIMO antennas	
Operating Frequency	700~960Mhz/1710~2690Mhz
Peak Gain	2dBi
Polarization	Linear
V.S.W.R.	≤2.0@ 1710 ~ 2700 MHz ≤2.5@ 700 ~ 960 MHz
Impedance	50Ω
GPS antenna	
Center Frequency	BeiDou:1561.098MHz GPS:1575.42MHz GLONASS:1602MHz
Band Width	±3MHZ
Peak Gain	3.0dBic (*Typical*) @ 1575.42 MHz
V.S.W.R.	<2.0
Polarization	RHCP
Impedance	50Ω
DC Voltage	2.7-5.0V
DC Current	8 ~14 mA
LNA Gain	28±2dB
Noise Figure	1.5dB
WIFI antenna	
Operating Frequency	2400~2483MHz/ 5150~5850MHz
Peak Gain	3dBi
Polarization	Linear

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



V.S.W.R.	≤2.0
Impedance	50Ω
Others	
Material of Plastic	PC+ABS
Dimension	Dia: 120mm
Cable Type	RG174H-02
Cable Length	3m
Connector Type	SMA Male
Operating Temp. & Humidity	-40℃~85℃ RH95%MAX
Storage Temp. & Humidity	-45℃~85℃ RH95%MAX

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

