

DMS Driver Status Monitoring System



—— Model No.: DMS31 ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

【Aberrant Behavior Detection and Alarm】

Fatigue detection, distraction detection, phone call detection, smoking detection, no driver detection, no mask detection, no seat belt detection, camera block detection, infrared blocking glasses detection, and drinking water detection, etc

【ID Recognition】

Driver identification, up to 400 certifications

【Remote Monitoring and Alarm】

The vehicle operation company can monitor the driver's status in real-time via the user platform. Should any abnormal behavior and status occur, the remote platform will send alarms automatically

【Audio Alarm & Video Alarm】

When aberrant driving behaviors are detected, the device will issue alarms and record the video

【All-whether Working Capability】

Strong adaptability to driving environment, working 24/7, not limited by weather conditions and daynight shift

【Auto Sensativity Adjustment】

Stop or start working according to vehicle speed

【WIFI Setting】

Can access parameter setting on mobile phone via WiFi connection

【Powerful Compatibility】

Support AHD/CVBS/fast ethernet output and RTSP, ISO17215 and other network protocols. Strong compatibility and wide application range

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

Power supply	10~32V DC
Power consumption	Max 4W
Built-in camera module parameters	FHD 1920x1080P/25f or 1920x1080P/30f
Video output	1CH, AHD, 1920x1080/25f or 1920x1080/30f
Video compression	H.264
Video record resolution	720P or 1080P
Recording parameters	The recording file is in MP4 format, 128G Micro SD card
Audio compression	ADPCM
WIFI module parameters	802.11b/g/n 150Mbps
Operating temperature	-20°C ~ +60°C
Storage temperature	-40°C ~ +85 °C
Dimension	110x86.5x64 mm
Weight	200g
GPS	YES
Speaker power	Max. 2W
Video output	AHD/CVBS/Fast ethernet
Network protocol	RTSP/ISO17215

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

