

6CH 1080P 360 Surround View Panoramic Image System



—— Model No.: BVA18P ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

【Compliant with UN ECE R151+R159, R158 regulations】

It meets the requirements of BSIS/MOIS/RVCS regulations, eliminating side, front and rear blindness of large vehicles

【6CH 360° Around View】

6CH 360° surround view image system, suitable for all kinds of vehicles

【One-minute Calibration】

Automatic calibration can be finished in 1 minute, and it supports automatic plane correction, saving time and effort

【Dual AI Cores】

Independent dual AI core processing with 2TOPS computing power delivers a smoother, more precise experience

【LDW+FCW+BSD】

Built-in AI algorithm, integrated with LDW+FCW+both sides BSD 360 degree detection, is able to detect lane departure, forward collision and overtaking/merging around the vehicle, and then to give an alarm

【Pedestrian Detection】

The control box is equipped with built-in processing capabilities, delivering more precise pedestrian detection. Each camera channel can cover a detection range of over 10 meters, providing comprehensive coverage with no blind spots

【DMS Driver Fatigue Monitoring】

Supports DMS algorithm, capable of monitoring driver fatigue

【Remote Vehicle Management】

It can be connected to the platform via 4G to achieve remote vehicle management

【Other Functions】

Optional capacitive touch screen; trigger wire and GPS access are both supported

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

Video input	Max.6CH×1080P AHD (25/30)FPS
Video output	1-CH 1080P AHD/VGA/CVBS(D1)/RTSP
Trigger input	1-CH backward trigger,1-CH let trigger, 1-CH right trigger, trigger 1/2/3 are extended input triggers for user-defined setting
TV System:	PAL /NTSC
Storage	Max. 1×512G SD card+1×2T SSD card
Waterproof rating	IP69K
Language	English,French,German. Dutch.Chinese
Power supply	10-32V
Operating current	<2A/12V
Operating temperature	-20℃ ~ 70℃
Storage temperature	-40℃ ~ 85℃
Operating humidity	10%-95%
Video input	Max.6CH×1080P AHD (25/30)FPS
Video output	1-CH 1080P AHD/VGA/CVBS(D1)/RTSP
Trigger input	1-CH backward trigger,1-CH let trigger, 1-CH right trigger, trigger 1/2/3 are extended input triggers for user-defined setting
TV System:	PAL /NTSC
Storage	Max. 1×512G SD card+1×2T SSD card
Waterproof rating	IP69K
Language	English,French,German. Dutch.Chinese
Power supply	10-32V
Operating current	<2A/12V
Operating temperature	-20℃ ~ 70℃

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

