

7-inch HD Quad-view Touchscreen Vehicle Monitoring Display



—— Model No.: HD140D ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- Waterproof Rating: IP66
- Supporting capacitive touch screen; Icon menu operation; Supporting some gestures
- Multiple video formats available to cameras: 1080P30/1080P25/720P30/720P25/PAL/NTSC, Quad-view display supported
- Supporting 4 CH HD camera input, display mode supports single view, dual views, triplex views, quad views, trefoil view, Y view, PIP view and other views
- the parameter of each CH image effect could be adjusted individually, supporting horizontal mirror image and vertical flip display
- 5 trigger lines input, trigger line definition, trigger delay and priority can be adjusted freely
- Automatic scan available, scanning channel and scanning time can be choosed
- Able to set reversing marking line, adjusting and calibrating freely.
- Backlight brightness supports 60-level manual adjustment and 3-level ambient light automobile adjustment
- Multi languages available
- 10-32V wide power supply input supports 12V or 24V automobile battery
- Easy to install and operate

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

System Format	PAL / NTSC
Resolution	1024x3(RGB)x600
Brightness	600 cd/m ²
Contrast	700:1
Viewing Angle	U: 85° / D: 85°, R/L: 85°
Aspect Ratio	16:9
Operating Temperature	-20~+70℃
Storage Temperature	-30~+80℃
Power Consumption	Max.25W
Power for Cameras	Max. 4×600mA, 12V
Power Supply	10V-32V
Dot Pitch	0.1506(H)x0.1432(V)
Video Input	4 CH
Audio Input	4 CH
Touch Screen Transmittance	≥ 80%
Operating Pressure	10~110g
Screen Response Time	<10ms

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

