

7 inch HD 2.4GHz Digital Wireless Vehicle Quad-view Monitor

1*Micro SD Card
(Max.128G)



—— Model No.: HDW127Q ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- Support 4CH wireless camera and wireless transmitter
- Display mode supports quad-view mode, split-view mode, single view mode, and the channels for the quad-view and split-view can be set flexibly
- With built-in recorder (supports 128GB Micro SD card), support 4CH real-time recording and video playback
- Supports both manual and automatic pairing
- Supporting 1080P/720P camera input
- Touch screen optional
- 5 trigger lines input, includes 4 channel single view trigger display and 1 channel split view trigger display, and the split view image can be set flexibly. In addition, trigger delay and priority can be adjusted freely.
- Support automatic brightness adjustment; screen brightness decreases automatically after the environment gets dark for 3 seconds.
- Automatic scan available, scanning channel and scanning time can be choosed.
- Support power fail safeguard by super-capacitor.
- Able to set reversing marking line, adjusting and calibrating freely.

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

LCD Dimension	7"
Resolution	1024x 3 (RGB) x600
Contrast	700:1
Brightness	600cd/m ²
Viewing Angle	U:80 / D:85, R/L:85
Pixel size	0.1506(W) x 0.1432(H)
Aspect Ratio	16:9
Channel	4 CH
Operating Frequency	2400MHz ~ 2483.5MHz(ISM band)
Receiving Sensitivity	-78dBm
Transmission power	FCC≤26dBm CE≤20dBm MIC≤10dBm
Receiving Sensitivity	H.264
Modulation	FHSS
Delay	200ms
Transmission Distance	FCC≤300 M CE≤200 M MIC≤60 M
Storage	Micro SD Card, up to 128GB
System Format	PAL / NTSC
Power Supply	DC 10-32V
Power Consumption	Max.10W
Loudspeaker	1W/8Ω
Operating temp. & humidity	-20~+70°C,RH90%MAX

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Storage temp. & humidity	-30~+80°C,RH90%MAX
--------------------------	--------------------

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

