

## 10.1 inch HD Digital Wireless Quad-view Monitor

1\*Micro SD Card(Max.128G)



—— Model No.: HDW295Q ——

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Features

- Support 4CH wireless camera and wireless transmitter
- Display mode supports quad-view mode, split-view mode, single view mode, and the channels for the quad-view and split-view can be set flexibly
- With built-in recorder (supports 128GB Micro SD card), support 4CH real-time recording and video playback
- Supports both manual and automatic pairing
- Supporting 1080P/720P camera input
- Touch screen optional
- 5 trigger lines input, includes 4 channel single view trigger display and 1 channel split view trigger display, and the split view image can be set flexibly. In addition, trigger delay and priority can be adjusted freely
- Support automatic brightness adjustment; screen brightness decreases automatically after the environment gets dark for 3 seconds
- Automatic scan available, scanning channel and scanning time can be choosed.
- Support power fail safeguard by super-capacitor
- Able to set reversing marking line, adjusting and calibrating freely

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Specification

|                            |                                    |
|----------------------------|------------------------------------|
| LCD Dimension              | 10.1"                              |
| Resolution                 | 1024x 3 (RGB) x600                 |
| Contrast                   | 600:1                              |
| Brightness                 | 600cd/m <sup>2</sup>               |
| Viewing Angle              | U:80 / D:85, R/L:85                |
| Aspect Ratio               | 16:9                               |
| Channel                    | 4 CH                               |
| Operating Frequency        | 2400MHz ~ 2483.5MHz(ISM band)      |
| Receiving Sensitivity      | -78dBm                             |
| Transmission power         | FCC≤26dBm<br>CE≤20dBm<br>MIC≤10dBm |
| Decompression Form         | H.264                              |
| Modulation                 | FHSS                               |
| Delay                      | 200ms                              |
| Transmission Distance      | FCC≤300 M<br>CE≤200 M<br>MIC≤60 M  |
| Storage                    | Micro SD Card, up to 128G          |
| System Format              | PAL / NTSC                         |
| Power Supply               | DC 10-32V                          |
| Power Consumption          | Max.10 W                           |
| Loudspeaker                | 1W/8Ω                              |
| Operating temp. & humidity | -20~+70°C,RH90%MAX                 |
| Storage temp. & humidity   | -30~+80°C,RH90%MAX                 |

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



**STONKAM CO., LTD**

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)

